



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Round ceiling recessed luminaire made from aluminium; opal PMMA cover; surface Black Matt; powder coated; matt texture; RAL 9005; installation without tools using blade springs; recessed depth 50 mm; suitable for ceiling thickness of 4-22 mm; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP44; Class 1; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



GENERAL

Ceiling _____

Recessed _____

Black Matt _____

RAL 9005 ^a _____

front IP44 _____

back IP20 _____


Interior _____

1060 lm _____

CIE flux code: 46 77 94 100 _____

100 _____

LIGHT DISTRIBUTION



LED

3000 K _____

CRI ≥ 90 _____

L80 / 60000h _____

initial MacAdam ≤ 3 SDCM _____

OPTICAL

Opal _____

ELECTRICAL

phase-cut dim _____

220 - 240 V _____

system 12.3 W _____

Class 1 _____

PHYSICAL

diameter 210 mm _____

height 48 mm _____

0.64 kg _____

wire springs _____

CUTOUT

diameter 202-205 mm _____

min. ceiling thickness 4 mm _____

max. ceiling thickness 22 mm _____

recessed depth 50 mm _____

^a Colour may deviate slightly due to production conditions.