




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Wall surface luminaire integrated in an acoustic element made of high quality PET felt with sound absorbing properties; 100% recyclable; surface Felt Oxide Red; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; indirect light distribution; 220 - 240 V; degree of protection IP20; Class 1; driver included;



GENERAL

Wall _____

Surface _____

Felt Oxide Red _____

IP20 _____

Interior _____

58 lm _____

CIE flux code: 17 42 70 50 100 _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000h _____

initial MacAdam ≤ 3 SDCM _____

ELECTRICAL

phase-cut dim _____

220 - 240 V _____

system 8.3 W _____

Class 1 _____

PHYSICAL


length 650 mm _____

width 120 mm _____

height 650 mm _____

1.67 kg _____

LIGHT DISTRIBUTION



[‘336174OF3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.94	0.91	0.87	0.84
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.