



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



GENERAL

Floor _____
 Surface _____
 Bronze _____
 IP65 _____
 Exterior _____
 250 lm _____
 CIE flux code: 50 87 99 100 _____
 100 _____

LED

2700 K _____
 CRI ≥ 90 _____
 L80 / 100000h _____
 initial MacAdam ≤ 3 SDCM _____


ELECTRICAL

24 V _____
 inset 4.5 W _____
 Class 3 _____

PHYSICAL

diameter 80 mm _____
 height 23 mm _____
 0.55 kg _____


LIGHT DISTRIBUTION



IP65



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; PCB 3-step binning; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 24 V; degree of protection IP65; Class 3; Plug & Play connector system; driver not included; inclusive 2500mm cable; ground spike included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[7381A2Q3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.


Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.94	0.93	0.91
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES
Plug & Play Driver

Type	Voltage	L·W·H (MM)	Item number
30W IP67	24V	118-35-26	90018014
75W IP67	24V	162,5-43-32	90018015

Plug & Play Extension Cable

Type	Length (MM)	Item number
2,5 m IP67	2500	90014502
5 m IP67	5000	90014503
0.5 m IP67	500	90014505
1 m IP67	1000	90014506

Plug & Play Straight Connector

Length (MM)	Item number
200	90014504

Plug & Play T-Connector

L·W·H (MM)	Item number
48-24-15	90014501