



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Square wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



GENERAL

Wall _____
 Recessed _____
 Anthracite Grey _____
 RAL 7016 ^a _____
 IP65 _____
 Exterior _____
 76 lm _____
 CIE flux code: 64 88 98 99 100 _____

LED

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Asymetric _____

ELECTRICAL

excl. driver _____
 24 V _____
 inset 2.4 W _____
 Class 3 _____

PHYSICAL


length 80 mm _____
 width 16 mm _____
 height 80 mm _____
 0.24 kg _____

CUTOUT

length 66 mm _____
 width 66 mm _____
 min. ceiling thickness 12 mm _____
 recessed depth 40 mm _____

^a Colour may deviate slightly due to production conditions.

LIGHT DISTRIBUTION



7451A2A5



MOUNTING ACCESSORIES

Concrete Housing

Type	L·W·H (MM)	Item number
ORIS 0.8 RETO 0.8	69-69-61	90012046

Recessed Housing incl. plasterkit

Type	L·W·H (MM)	Item number
ORIS 0.8 RETO 0.8	109-109-74	90012047

ELECTRICAL ACCESSORIES

Driver

Type	Voltage	L·W·H (MM)	Item number
35W 24V IP67	24V	175-31-43	90212802
100W 24V IP67	24V	178-68-39	90212903